



**Herstellereklärung
 Manufacturer Statement**

ASO[®]-Unigrund-S

Information zu umweltbezogenen Aspekten für DGNB (NBV12 / NBV15) und LEED[®] (v3/v4) Kriterien.
 Hierfür werden untenstehende Produktangaben in Bezug auf die DGNB und LEED[®] Kriterien gemacht:

	DGNB und LEED [®] relevante Eigenschaften
VOC-Gehalt	Der VOC-Gehalt im gebrauchsfertigen Zustand gemäß 2004/42/EG beträgt 0 %. Der VOC-Gehalt abzüglich Wasser beträgt 0 g/l. Der zulässige Grenzwert in der Kategorie ‚Primers, Sealers and Undercoaters‘ gemäß SCAQMD Rule 1113 ist 100 g/l.
GISCODE	Das Produkt gehört zur Gruppe GISCODE: M-GP01
EMICODE	Das Produkt erfüllt die Anforderungen für den EMICODE: EC 1 Plus Die Anforderungen des AgBB-Schemas sind erfüllt. Der Formaldehydgehalt ist < 10 µg/m ³ nach 28 Tagen. Der Lösemittelanteil beträgt 0 % (0 g/l). Der TVOC Bereich nach 14 Tagen ist: 0,5 mg/m ³ und 5,0 mg/m ³ .
Lösemittel- und weichmacherfrei nach VdL-RL 01	Das Produkt ist lösemittel- und weichmacherfrei gemäß VdL-RL 01.
Brandfall	Das Produkt führt im Brandfall nicht zu ätzenden oder zersetzenden Rauchgasen.
EPD – Branchenweite generische Umweltproduktdeklaration	Für das Produkt liegt eine industrieweite, generische Umweltproduktdeklaration vor. Deklarationsnummer: EPDDIV20140100IBG1DE EPD Programm Betreiber: Institut Bauen und Umwelt

Information in terms of environmental issues according LEED[®] (v3/v4) and DGNB (NBV12 / NBV15):
 For this purpose, below product specifications in terms of LEED[®] and DGNB are specified:

	DGNB and LEED [®] relevant properties
VOC-Content	The VOC-content is 0 %. The VOC-content less water is 0 g/l. The valid VOC-limit in the category ‚Primers, Sealers and Undercoaters‘ according to SCAQMD Rule 1113 is 100 g/l.
GISCODE	The product belongs to the group GISCODE: M-GP01
EMICODE	The product meets the requirements for EMICODE: EC 1 Plus The requirements of the AgBB scheme are fulfilled. The content of formaldehyde is < 10 µg/m ³ at 28 days. The content of solvent is 0 % (0 g/l). The TVOC Range after 14 days is: 0.5 mg/m ³ and 5.0 mg/m ³ .
Free of solvents and softeners according to VdL-RL 01	The product is free of solvents and softeners according to VdL-RL 01.
Fire Risks	The product does not lead to toxic or corrosive fumes in case of fire.
EPD – Industry-wide (generic) environmental product declaration	For the product exists an industry-wide (generic) environmental product declaration. Number of declaration: EPDDIV20140100IBG1DE EPD Program Operator: Institut Bauen und Umwelt